

# JE24U2LT10-3


## 2-Line Uni-directional TVS Diode



### Description


The JE24U2LT10-3 is a Uni-directional TVS diode, utilizing leading monolithic silicon technology to provide fast response time and low ESD clamping voltage, making this device an ideal solution for protecting voltage sensitive data and power line. The JE24U2LT10-3 complies with the IEC 61000-4-2 (ESD) standard with  $\pm 30$  kV air and  $\pm 30$  kV contact discharge. It is assembled into an ultra-small lead-free SOT-23 package. The small size and high ESD surge protection make JE24U2LT10-3 an ideal choice to protect cell phone, digital cameras, audio players and many other portable applications.

### Circuit Diagram



Circuit and Pin Schematic

### Marking Diagram



Transparent top view

S24:Device Marking Code

### Features

- \* 300W peak pulse power (8/20 $\mu$ s)
- \* Low leakage: nA level
- \* Operating voltage: 24V
- \* Low clamping voltage
- \* Two power line protects
- \* Complies with following standards:
  - IEC 61000-4-2 (ESD) immunity test
  - Air discharge:  $\pm 30$ kV
  - Contact discharge:  $\pm 30$ kV
  - IEC61000-4-5 (Lightning) 5A (8/20 $\mu$ s)
- \* RoHS Compliant
- \* Package: SOT-23

### Applications

- \* Cellular Handsets and Accessories
- \* Personal Digital Assistants
- \* Notebooks and Handhelds
- \* Digital Cameras
- \* Set Top Box
- \* Industrial Cotrols
- \* Server and Deskop PC

### Ordering Information

Part Number	Packaging	Reel Size
JE24U2LT10-3	3000/Tape & Reel	7 inch

### Absolute Maximum Ratings ( $T_A=25^{\circ}\text{C}$ unless otherwise specified)


Parameter	Symbol	Value	Unit
Peak Pulse Power (8/20 $\mu\text{s}$ )	Ppk	300	W
Peak Pulse Current (8/20 $\mu\text{s}$ )	IPP	5	A
ESD per IEC 61000-4-2 (Air)	VESD	$\pm 30$	kV
ESD per IEC 61000-4-2 (Contact)		$\pm 30$	
Operating Temperature Range	TJ	-55to +125	$^{\circ}\text{C}$
Storage Temperature Range	Tstg	-55 to +150	$^{\circ}\text{C}$

### Electrical Characteristics ( $T_A=25^{\circ}\text{C}$ unless otherwise specified)


Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Reverse Working Voltage	$V_{\text{RWM}}$				5	V
Breakdown Voltage	$V_{\text{BR}}$	$I_{\text{T}} = 1\text{mA}$	27			V
Reverse Leakage Current	$I_{\text{R}}$	$V_{\text{RWM}} = 24\text{V}$			0.2	$\mu\text{A}$
Clamping Voltage	$V_{\text{C}}$	$I_{\text{PP}} = 1\text{A}$ (8 x 20 $\mu\text{s}$ pulse)			40	V
Clamping Voltage	$V_{\text{C}}$	$I_{\text{PP}} = 5\text{A}$ (8 x 20 $\mu\text{s}$ pulse)			60	V
Junction Capacitance	$C_{\text{J}}$	$V_{\text{R}} = 0\text{V}$ , $f = 1\text{MHz}$ , Pin 1 to pin 3 or Pin 2 to Pin 3			50	pF
Junction Capacitance	$C_{\text{J}}$	$V_{\text{R}} = 0\text{V}$ , $f = 1\text{MHz}$ , Pin 1 to pin 2			25	pF

### Portion Electronics Parameter


Symbol	Parameter
$I_{\text{T}}$	Test Current
$I_{\text{PP}}$	Maximum Reverse Peak Pulse Current
$V_{\text{C}}$	Clamping Voltage @ $I_{\text{C}}$




## Typical Performance Characteristics ( $T_A=25^\circ\text{C}$ unless otherwise Specified)




Junction Capacitance vs. Reverse Voltage




Clamping Voltage vs. Peak Pulse Current




Peak Pulse Power vs. Pulse Time



IEC61000-4-2 Pulse Waveform




Power Derating Curve




8 X 20us Pulse Waveform

## SOT-23 Package Outline Drawing (Dimensions in millimeters)



SYM	DIMENSIONS					
	MILLIMETERS			INCHES		
	MIN	NOM	MAX	MIN	NOM	MAX
A	0.90	--	1.15	0.035	--	0.045
A1	0.00	--	0.10	0.000	--	0.004
A2	0.90	--	1.05	0.035	--	0.041
b	0.30	--	0.50	0.012	--	0.020
c	0.08	--	0.15	0.003	--	0.006
D	2.80	--	3.00	0.110	--	0.118
E	1.20	--	1.40	0.047	--	0.055
E1	2.25	--	2.25	0.089	--	0.100
e	0.95TYP			0.037TYP		
e1	1.80	--	2.00	0.071	--	0.079
L	0.55REF			0.022REF		
L1	0.30	--	0.50	0.012	--	0.020
Θ	0°	--	8°	0°	--	8°

## Suggested Land Pattern



SYM	DIMENSIONS	
	INCHES	MILLIMETERS
C	(.087)	(2.20)
E	.037	0.95
E1	.075	1.90
G	.031	0.80
X	.039	1.00
Y	.055	1.40
Z	.141	3.60

## NOTICE

Jelan-Link reserves the right to make changes without further notice to any products here in.

Only obligations are those in the Jelam-Link Standard Terms and Conditions of Sale and in no case will Jelam-Link be liable for any incidental, indirect, or consequential damages arising from the sale, resale, use, or misuse of its products.