


Description

The JS05U1GS30-2 is a uni-directional TVS diode, utilizing leading monolithic silicon technology to provide fast response time and low ESD clamping voltage, making this device an ideal solution for protecting voltage sensitive data and power line. The JS05U1GS30-2 complies with the IEC 61000-4-2 (ESD) standard with $\pm 30\text{kV}$ air and $\pm 30\text{kV}$ contact discharge. It is assembled into an ultra-small lead-free SOD-323 package. The small size and high ESD surge protection make JS05U1GS30-2 an ideal choice to protect cell phone, digital cameras, audio players and many other portable applications.

Features

- * Protects one data or power line
- * Ultra low leakage: nA level
- * Operating voltage: 5 V
- * Low clamping voltage
- * 2-pin leadless package
- * Complies with following standards:
 - IEC 61000-4-2 (ESD) immunity test
 - Air discharge: $\pm 30\text{kV}$
 - Contact discharge: $\pm 30\text{kV}$
 - IEC61000-4-5 (Lightning) 90A (8/20 μs)
- * RoHS Compliant
- * Package: SOD-323

Circuit Diagram



Circuit Diagram

Applications

- * Mobile Phones
- * Battery Protection
- * Power Line Protection
- * Vbat pin for Mobile Devices
- * Hand Held Portable Applications

Marking Diagram



Transparent top view

57D:Device Marking Code

Ordering Information

Part Number	Packaging	Reel Size
JS05U1GS30-2	3000/Tape & Reel	7 inch

Absolute Maximum Ratings ($T_A=25^{\circ}\text{C}$ unless otherwise specified)


Parameter	Symbol	Value	Unit
Peak Pulse Power (8/20 μs)	Ppk	1800	W
Peak Pulse Current (8/20 μs)	IPP	90	A
ESD per IEC 61000-4-2 (Air)	VESD	± 30	kV
ESD per IEC 61000-4-2 (Contact)		± 30	
Operating Temperature Range	TJ	-55 to +125	$^{\circ}\text{C}$
Storage Temperature Range	Tstg	-55 to +150	$^{\circ}\text{C}$

Electrical Characteristics ($T_A=25^{\circ}\text{C}$ unless otherwise specified)


Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Reverse Working Voltage	V_{RWM}				5.0	V
Breakdown Voltage	V_{BR}	$I_{\text{T}} = 1\text{mA}$	6.5	7.5	8.5	V
Reverse Leakage Current	I_{R}	$V_{\text{RWM}} = 5.0\text{V}$			0.5	μA
Clamping Voltage	V_{C}	$I_{\text{PP}} = 1\text{A}$ (8 x 20 μs pulse)			8.0	V
Clamping Voltage	V_{C}	$I_{\text{PP}} = 90\text{A}$ (8 x 20 μs pulse)			20	V
Junction Capacitance	C_{J}	$V_{\text{R}} = 0\text{V}$, $f = 1\text{MHz}$		450	500	pF

Portion Electronics Parameter


Symbol	Parameter
I_{T}	Test Current
I_{PP}	Maximum Reverse Peak Pulse Current
V_{C}	Clamping Voltage @ I_{C}




Typical Performance Characteristics ($T_A=25^{\circ}\text{C}$ unless otherwise Specified)




Junction Capacitance vs. Reverse Voltage




Clamping Voltage vs. Peak Pulse Current




Peak Pulse Power vs. Pulse Time



IEC61000-4-2 Pulse Waveform




Power Derating Curve




8 X 20us Pulse Waveform

SOD-323 Package Outline Drawing



SYM	DIMENSIONS			
	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	1.50	1.80	0.060	0.071
B	1.20	1.40	0.045	0.054
C	2.30	2.70	0.090	0.107
D	-	1.10	-	0.043
E	0.30	0.40	0.012	0.016
F	0.10	0.25	0.004	0.010
H	-	0.10	-	0.004

Suggested Land Pattern



SYM	DIMENSIONS	
	MILLIMETERS	INCHES
A	3.15	0.120
B	0.80	0.031
C	0.80	0.031

NOTICE

Jelan-Link reserves the right to make changes without further notice to any products here in.

Only obligations are those in the Jelam-Link Standard Terms and Conditions of Sale and in no case will Jelam-Link be liable for any incidental, indirect, or consequential damages arising from the sale, resale, use, or misuse of its products.